

ASME B16.47 A Class 600 Flange Datasheet

Nominal Bore (in / mm)	Full Face Gasket				IBC Gasket
	OD x ID (mm)	No. of Bolt Holes	Hole Diameter (mm)	Bolt PCD (mm)	OD x ID (mm)
22 / 550	870 x 559	24	48	778	733 x 559
26 / 650	1016 x 660	28	51	914	867 x 660
28 / 700	1073 x 711	28	54	965	914 x 711
30 / 750	1130 x 762	28	54	1022	972 x 762
32 / 800	1194 x 813	28	60	1080	1022 x 813
34 / 850	1245 x 864	28	60	1130	1073 x 864
36 / 900	1314 x 914	32	67	1194	1130 x 914
38 / 950	1270 x 965	32	60	1162	1105 x 965
40 / 1000	1321 x 1016	32	60	1213	1156 x 1016
42 / 1050	1403 x 1067	32	67	1283	1219 x 1067
44 / 1100	1454 x 1118	32	67	1334	1270 x 1118
46 / 1150	1511 x 1168	28	67	1391	1327 x 1168
48 / 1200	1594 x 1219	32	73	1461	1391 x 1219
50 / 1250	1670 x 1270	32	79	1524	1448 x 1270
52 / 1300	1721 x 1321	32	79	1575	1499 x 1321
54 / 1350	1778 x 1372	28	79	1632	1556 x 1372
56 / 1400	1854 x 1422	28	86	1695	1613 x 1422
58 / 1450	1905 x 1473	32	86	1746	1664 x 1473
60 / 1500	1994 x 1524	32	92	1810	1721 x 1524

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.