

Rubber Threshold Ramps Datasheet

Product Code: RC1142

Product Description

Crafted entirely from 100% recycled rubber with a 1:10 gradient, these rubber threshold ramps boast exceptional strength and versatility for both indoor and outdoor use. Their robust construction ensures durability, non-slip properties, and hassle-free installation and upkeep. Available in a range of sizes from 12mm to 80mm.

Size Specifications

Property	Value
Length (mm)	120 - 800
Width (mm)	500 - 1000
Height (mm)	12 - 80
Weight (kg)	1.6 - 25.6
Capacity (kg)	1000



Key Features

- Seamless gradient designed for disabled access, offering a 1 in 10 slope
- Robust rubber ramp with a capacity of 1000kg, suitable for wheelchairs, scooters, and walkers
- All-weather access ramp usable indoors and outdoors, resilient enough for outdoor storage
- No installation necessary; simply place the rubber ramp beside the step or curb and it's ready for use
- Anti-slip surface ensures optimal traction and safety during use
- Easily adjust the ramp's width using a Stanley knife, saw, or similar tool
- Expand the width as needed—its flat edge design allows multiple ramps to be placed side by side
- Crafted from 100% recycled rubber compound for eco-friendly usability

Single ramps measuring up to 70mm are available for purchase individually in 1-metre wide pieces. Ramps starting from 74mm and higher are sold as a pair, comprising two ramps each 500mm wide. For heights exceeding 80mm, we recommend exploring our Rubber Threshold Ramps selection, offering heights up to 7"/177.8mm.

Please be aware that the natural odour of rubber dissipates within a few days when exposed to fresh air. To speed this process, wipe the surface with a damp cloth containing washing up liquid.



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Size Variations

Thicknesses	Values
12mm/0.47"	Length (mm): 120
	Width (mm): 1000
	Weight (kg): 1.60
	Capacity (kg): 1000
16mm/0.62"	Length (mm): 160
	Width (mm): 997
	Weight (kg): 2.6
	Capacity (kg): 1000
20mm/0.78"	Length (mm): 146
	Width (mm): 1000
	Weight (kg): 2.3
	Capacity (kg): 1000
24mm/0.94"	Length (mm): 240
	Width (mm): 994
	Weight (kg): 3.9
	Capacity (kg): 1000
28mm/1.1"	Length (mm): 280
	Width (mm): 996
	Weight (kg): 4.8
	Capacity (kg): 1000
30mm/1.18"	Length (mm): 300
	Width (mm): 1000
	Weight (kg): 6.2
	Capacity (kg): 1000
32mm/1.25"	Length (mm): 320
	Width (mm): 900
	Weight (kg): 6
	Capacity (kg): 1000
36mm/1.42"	Length (mm): 360
	Width (mm): 990
	Weight (kg): 8.2
	Capacity (kg): 1000

Size Variations

Thicknesses	Values
40mm/1.57"	Length (mm): 400
	Width (mm): 1000
	Weight (kg): 9.1
	Capacity (kg): 1000
44mm/1.73"	Length (mm): 440
	Width (mm): 1000
	Weight (kg): 9.7
	Capacity (kg): 1000
48mm/1.88"	Length (mm): 480
	Width (mm): 1000
	Weight (kg): 10.9
	Capacity (kg): 1000
50mm/1.97"	Length (mm): 500
	Width (mm): 1000
	Weight (kg): 11.8
	Capacity (kg): 1000
52mm/2.04"	Length (mm): 520
	Width (mm): 1000
	Weight (kg): 13.1
	Capacity (kg): 1000
56mm/2.20"	Length (mm): 560
	Width (mm): 1000
	Weight (kg): 13.6
	Capacity (kg): 1000
60mm/2.36"	Length (mm): 600
	Width (mm): 1000
	Weight (kg): 16.3
	Capacity (kg): 1000
65mm/2.55"	Length (mm): 650
	Width (mm): 1000
	Weight (kg): 19.2
	Capacity (kg): 1000

Size Variations

Thicknesses	Values
70mm/2.76"	Length (mm): 700
	Width (mm): 1000
	Weight (kg): 19.9
	Capacity (kg): 1000
74mm/2.91"	Number of ramps: 2
	Length (mm): 780
	Width per ramp (mm): 500
	Total width (mm): 1000
	Weight per ramp (kg): 12.40
	Weight per pair (kg): 24.80
	Capacity per ramp (kg): 500
	Capacity across the pair (kg): 1000
78mm/3.07"	Number of ramps: 2
	Length (mm): 780
	Width per ramp (mm): 500
	Total width (mm): 1000
	Weight per ramp (kg): 12.65
	Weight per pair (kg): 25.3
	Capacity per ramp (kg): 500
	Capacity across the pair (kg): 1000
80mm/3.14"	Number of ramps: 2
	Length (mm): 800
	Width per ramp (mm): 500
	Total width (mm): 1000
	Weight per ramp (kg): 12.8
	Weight per pair (kg): 25.6
	Capacity per ramp (kg): 500
	Capacity across the pair (kg): 1000

Technical Data

Thicknesses	Values
Capacity (kg)	1000
Height (mm)	12 - 80
Length (mm)	120 - 800
Weight (kg)	1.6 - 25.6
Width (mm)	500 - 1000
One Year Warranty	Yes
Easy to Fit	Yes
Electric Wheelchair	Yes
Manual Wheelchair	Yes
Mobility Scooter Friendly	Yes
Leave Outside	Yes