

Acrylic Tissue Tape Datasheet

Product Code: RC13-PSA-8441

Food Contact Information

Based on supplier information the raw materials used in producing the adhesive tape conform to the compositional requirements of FDA 175.105 for indirect food contact. Additional to this compliance there should also be a functional barrier between adhesive and the food. Such functional barrier and determination of suitability are the responsibility of the customer.

Technical Specification

Property	Value
Material	Acrylic Tissue Tape
Available Thicknesses	115 Micron
Liner	80g Brown Siliconised Release Paper
Carrier	13g Tissue
Adhesive	Acrylic based with 45gsm on both open and closed sides
Total Thickness	115 micron
Peel Adhesion to Steel (24-hour dwell)	protected 650 N/M
Shear adhesion to steel:	protected 50 hours open 50 hours
Service temperature range:	-10°C to 180°C
Recommended application temperature range:	5°C to 60°C
Continuous operating temperature range:	25°C
Shelf Life:	Recommended 12 months from supply
Widths:	3mm, 6mm, 9mm, 12mm, 25mm, 50mm, 1000mm (other widths available)
Lengths:	10m, 25m, 50m, 100m, 250m (other lengths available)



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.