The RUBBER company

Manufactures • Designers • Distributors

Experts in Rubber

Web Tack Aerosol Adhesive Data

Web Tack is an aerosol adhesive, which does not contain CFC's, or 1.1.1 Trichloroethane. It bonds a wide variety of materials giving rapid bond formation and is economical in use.

- Halogen and CFC free
- Fast Tack
- Foaming formula for low soak in
- Economical in use
- Variable spray

Web Tack bonds a wide variety of substrates including wood, concrete, stone, tiles, rubber, foam, metals, rigid plastics, polyethylene, canvas fabrics, cardboard, paper and cork.

Web Tack is ideal for fixing polyethylene sheeting for enclosures prior to asbestos removal, for fixing thermal insulation and for packaging applications such as palletising or case sealing. It may be used for foam bonding, upholstery, automotive, carpets and trim and is useful for temporary bonding instead of double sided tapes.

Not suitable for use with plasticised PVC or expanded polystyrene.

TECHNICAL DATA:

Type:	Aerosol Adhesive
Colour:	Straw
Base:	Synthetic Rubber/Resin
Application:	Aerosol Spray
Application Temp:	+5°C to +40°C
Drying Time:	2-5 minutes
Clean Up:	Solvent Cleaner or white spirit
Storage Life:	12 months
Packaging:	500ml aerosol cans

APPLICATION:

Shake before use. Spray adhesive from 6" – 8" away onto one or both surfaces. Surfaces should be clean, dry and free from grease. For one-way application let adhesive dry for 30 seconds until tacky, then press into position. For two-way application, spray both surfaces and allow to dry for 2–5 minutes before bonding.

For temporary bonding, spray one surface and allow to dry for 2 – 5 minutes before bonding. Excess adhesive can be removed with a solvent cleaner or white spirit. To prevent spray nozzle from blocking, at the end of each period of use, turn the can upside down and press nozzle until spray is clear of adhesive.

HEALTH AND SAFETY DATA: Full material safety data sheets are available on request.

IMPORTANT NOTE:

All the information in this data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for his purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.

ADDRESS
Frys Cross Farm, Knightons Lane
Dunsfold, Surrey, GU8 4NY
United Kingdom

TELEPHONE
+44 (0)1483 801 210
Skype: therubberco

WEB
E sales@therubbercompany.com
W www.therubbercompany.com

The information contained on this product information sheet is to be used as guidance only. The advice and technical data given is done so in good faith and does not constitute any warranty or guarantee on product performance or suitability. We hereby reserve the right to change the technical information herewith without notification or prior agreement.