

Grey Flexible Flame Resistant Hose Datasheet

Product Code: RC07-I-132

Product Description

Grey flexible hose made of flame-resistant PVC coated polyester fabric , reinforced with a steel spiral embedded between the two layers.

Technical Specification

Ø INT.	Weight	Bending	Coil Length	Volume
mm	g/m	mm	m	m ³
40*	115	20	10	0.002
45	125	23	10	0.002
51*	135	26	10	0.003
55	145	28	10	0.003
60*	160	30	10	0.004
63*	165	32	10	0.004
65	170	33	10	0.005
70	165	35	10	0.005
73	175	37	10	0.006
76*	180	38	10	0.006
80*	190	40	10	0.007
82	195	41	10	0.007
90	210	45	10	0.009
102*	275	51	10	0.011
107	290	54	10	0.012
110	300	55	10	0.013
115	310	58	10	0.014
120*	325	60	10	0.015
125	340	63	10	0.016
127*	345	64	10	0.017
130	350	65	10	0.018
140*	380	70	10	0.021
152*	410	76	10	0.024
160*	420	80	10	0.027

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Data

Ø INT.	Weight	Bending	Coil Length	Volume
mm	g/m	mm	m	m ³
163	430	82	10	0.028
170	445	85	10	0.030
180	475	90	10	0.034
200	525	100	10	0.041
203*	535	102	10	0.043
228	600	114	10	0.054
230	600	115	10	0.055
254*	840	127	10	0.067
279	920	140	10	0.080
305	1005	153	10	0.124
310	1020	155	10	0.099
315	1040	158	10	0.102
330	1090	165	10	0.112
356	1175	178	10	0.130
406*	1335	203	10	0.168
455	1875	228	10	0.211
500	2055	250	10	0.255
505	2080	253	10	0.260

The technical data here reported has been measured at 23°C with 50% humidity.

*Sizes highlighted in green are available from stock.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.