

## Grey PVC-P Spiral Hose Datasheet

Product Code: RC07-I-118

### Product Description

Grey PVC-P spiral hose, reinforced with an anti-shock rigid PVC spiral.

### Technical Specification

∅ INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm/inch	mm	mm	g/m	m H <sup>2</sup> O	mm	m	m <sup>3</sup>
13	0.8	2.8	90	4.5	20	30	0.019
16	0.8	2.8	110	4.5	20	30	0.025
19.1	0.8	2.8	130	4	30	30	0.032
20*	0.8	2.8	140	4	30	30	0.036
22	0.8	2.8	150	4	30	30	0.036
25*	1	2.9	190	4	40	50	0.073
30	1	3	230	3.5	50	50	0.115
31.8*	1	3.1	260	3.5	50	50	0.122
35	1	3.3	290	3.5	50	50	0.133
38.1*	1	3.5	340	3	60	50	0.144
39	1	3.5	340	3	60	50	0.177
40*	1	3.5	350	3	60	50	0.180
45	1	3.8	440	3	70	50	0.202
50*	1	4.1	520	3	80	50	0.251
51.5	1	4.1	540	3	80	50	0.258
50.8*	1	4.1	530	3	80	50	0.255
55	1	4.2	590	3	80	50	0.274
60*	1	4.2	640	3	90	50	0.394
63.5	1	4.2	680	3	100	50	0.414
65	1	4.2	690	3	100	50	0.423
70	1.2	4.5	750	3	110	50	0.455
76.2	1.2	4.6	840	2.5	110	50	0.615
77.7	1.2	4.6	860	2.5	120	50	0.626

*The technical data here reported has been measured at 23°C with 50% humidity.*

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

### Technical Specification

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm/inch	mm	mm	g/m	m H <sup>2</sup> O	mm	m	m <sup>3</sup>
80	1.2	5.1	960	2.5	120	50	0.649
90	1.2	5.3	1140	2.5	140	30	0.435
100*	1.2	5.8	1330	2.5	150	30	0.643
102	1.2	5.8	1350	2.5	150	30	0.654
103.5	1.2	5.8	1370	2.5	150	30	0.663
105	1.2	5.8	1390	2.5	160	30	0.672
110	1.3	5.9	1470	2.5	160	30	0.702
120	1.3	5.9	1600	2.5	180	30	0.759
127	1.3	6	1720	2.5	190	30	0.801
130	1.3	6	1760	2.5	190	30	0.818
140	1.3	6.1	1940	2	200	30	1.169
151.5	1.3	6.4	2110	2	220	20	1.262
152.4	1.3	6.4	2130	2	220	20	1.269
160	1.5	7	2330	1.5	230	20	1.336
180	1.5	7	2620	1.5	250	20	1.490
200*	1.5	7.3	2900	1.5	280	20	1.648
203.2	1.5	7.3	2940	1.5	280	20	1.673
250	1.5	7.6	3800	1	330	10	1.358
300	1.5	7.6	4700	1	380	10	1.616

\*Sizes highlighted in green are available from stock.

*The technical data here reported has been measured at 23 °C with 50% humidity.*

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.