

## Light Blue PVC-P Spiral Hose Datasheet

Product Code: RC07-I-130

### Product Description

Light blue PVC-P spiral hose, reinforced with an anti-shock rigid PVC spiral.

### Technical Specification

∅ INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	m H <sup>2</sup> O	mm	m	m <sup>3</sup>
16	1.2	2.6	130	6	65	50	0.037
19.1	1.2	2.6	150	6	65	50	0.049
20	1.2	2.6	150	6	80	50	0.051
25	1.2	2.6	190	6	100	50	0.072
30	1.4	3	270	6	110	50	0.115
31.8	1.4	3.1	300	6	120	50	0.122
35	1.5	3.2	330	5	130	50	0.32
38.1	1.5	3.2	360	5	135	50	0.142
39	1.5	3.2	370	5	140	50	0.145
40	1.5	3.2	380	5	160	50	0.178
45	1.6	3.4	460	5	175	50	0.199
50	1.6	3.9	570	5	175	50	0.250
51.5	1.6	3.9	580	5	180	50	0.256
50.8	1.6	3.9	580	5	175	50	0.253
55	1.7	4	650	5	190	50	0.272
57	1.7	4	680	5	200	50	0.374
60	2	4.6	880	5	220	50	0.399
63.5	2	4.6	930	5	230	50	0.419
65	2	4.6	950	5	250	50	0.427
70	2	5.2	1070	5	270	50	0.463
76.2	2	5.2	1160	5	290	30	0.624
80	2	5.4	1220	5	350	30	0.523
90	2	5.4	1360	4.5	400	30	0.581
100	2.1	5.6	1520	4.5	400	30	0.641
102	2.1	5.6	1550	4.5	430	30	0.652
110	2.1	6.2	1810	4.5	470	30	0.705

*The technical data here reported has been measured at 23°C with 50% humidity.*

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

### Technical Data

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	m H <sup>2</sup> O	mm	m	m <sup>3</sup>
120	2.1	6.3	2000	4.5	500	30	1.018
127	2.2	6.5	2220	4.5	510	30	1.075
130	2.3	6.8	2430	4	560	30	1.103
140	2.3	7	2700	4	600	20	1.183
151.5	2.5	7.3	3010	4	600	20	1.276
152.4	2.5	7.4	3080	4	650	20	1.284
160	2.7	8	3320	3.5	730	20	1.408
180	2.7	8	3720	3.5	800	20	1.568
200	2.7	8	3960	3.5	800	20	1.728
203.2	2.7	8	4020	3	1250	10	1.754
250	2.8	8.4	5260	7	1500	10	2.134

*The technical data here reported has been measured at 23°C with 50% humidity.*

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.