

Lightest Blue PVC-P Spiral Hose Datasheet

Product Code: RC07-I-131

Product Description

Light blue PVC-P spiral hose, reinforced with an anti-shock rigid PVC spiral.

Technical Specification

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	m H ² O	mm	m	m ³
25	0.6	2.5	140	0.8	30	30	0.039
27	0.6	2.5	150	0.8	40	30	0.052
30	0.6	2.5	160	0.8	40	30	0.061
31.8	0.7	2.5	180	0.7	40	30	0.061
35	0.7	2.6	200	0.7	40	30	0.087
38.1	0.7	2.6	210	0.7	50	30	0.094
39	0.7	2.7	230	0.7	55	30	0.112
40	0.7	2.7	230	0.7	50	30	0.114
45	0.7	2.7	260	0.7	80	30	0.145
50	0.7	2.9	300	0.7	90	30	0.161
51.5	0.7	2.9	310	0.7	90	30	0.165
50.8	0.7	2.9	310	0.7	90	30	0.163
55	0.7	3.1	360	0.7	95	30	0.176
60	0.7	3.4	440	0.6	100	30	0.192
63.5	0.7	3.5	490	0.6	100	30	0.203
65	0.7	3.5	500	0.6	100	30	0.311
70	0.7	3.8	520	0.5	110	30	0.335
76.2	0.7	3.8	560	0.5	120	30	0.362
77.7	0.7	3.8	570	0.5	120	30	0.368
80	0.8	4	620	0.5	130	30	0.380
90	0.8	4.1	720	0.4	150	30	0.424
100	0.8	4.3	800	0.4	160	30	0.626
102	0.8	4.3	810	0.4	160	30	0.637
103.5	0.8	4.3	820	0.4	170	30	0.646
110	0.8	4.7	950	0.4	190	30	0.688
120	0.8	4.8	1060	0.4	200	30	0.746

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Data

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	m H ² O	mm	m	m ³
127	0.8	4.9	1160	0.3	230	30	0.985
130	0.8	5.1	1260	0.3	250	30	1.009
140	0.8	5.1	1360	0.3	260	30	1.081
151.5	0.9	5.5	1580	0.3	280	20	0.936
152.4	0.9	5.6	1630	0.3	280	20	0.942
160	1	6.1	1770	0.2	280	20	0.992
180	1	6.1	1980	0.2	450	20	1.476
200	1	6.6	2310	0.2	600	20	1.637
203.2	1	6.6	2350	0.2	600	20	1.662

The technical data here reported has been measured at 23 °C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.