宇航橡胶 YuHang Rubber RUBBER

南京宇航橡胶有限公司

NANJING YUHANG RUBBER CO.LTD

Manufacturers · Designers · Distributors

Translucent Ester-Based TPU Hose Datasheet

Product Code: RC07-I-183

Product Description

Translucent, ester-based TPU hose, reinforced with TPU-coated copper-coloured steel spiral.

Technical Specification

Ø INT.	Min Wall Th.	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	g/m	m H^2O	mm	m	m^3
20	1.5	345	9.5	25	20	0.031
25	1.5	305	9.5	30	20	0.048
30	1.5	440	9.5	35	20	0.056
32	1.5	465	9.5	35	20	0.059
35	1.5	500	9.5	40	20	0.063
38	1.5	535	9.5	40	20	0.091
40	1.5	560	9.5	50	20	0.095
45	1.5	620	9	50	20	0.104
50	1.5	685	9	60	20	0.114
51	1.5	695	9	60	20	0.116
55	1.5	745	9	65	20	0.124
60	1.5	810	8.5	70	20	0.133
63	1.5	845	8	70	20	0.185
65	1.5	870	7.5	70	20	0.190
70	1.5	1005	7.5	80	20	0.205
75	1.5	1075	8	80	20	0.218
76	1.5	1090	8	90	20	0.248
80	1.5	1140	6	90	20	0.259
90	1.5	1275	5	100	20	0.288
100	1.5	1410	4	120	15	0.317
102	1.5	1435	3.5	120	15	0.323
110	1.5	1545	3.2	130	15	0.346
115	1.5	1610	3	135	15	0.360
120	1.5	1675	3	140	15	0.374
122	1.5	1705	3	140	15	0.380
127	1.5	2075	2.9	150	15	0.397
130	1.5	2120	2.6	150	15	0.608

The technical data here reported has been measured at 23 °C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255

Nanjing YuHangrubber company limited in China Jiangshu

Technical Specification

Ø INT.	Min Wall Th.	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	g/m	m H^2O	mm	m	m^3
140	1.5	2275	2.4	160	15	0.651
150	1.5	2435	2	170	15	0.695
152	1.5	2465	2	170	15	0.703
160	1.5	2590	1.8	180	15	0.738
175	1.5	2705	1.5	200	15	0.954
180	1.5	2780	1.5	210	15	0.980
200	1.5	3080	1.2	230	15	1.082
203	1.5	3125	1.2	230	15	1.098
206	1.5	3170	1.2	235	15	1.113
220	1.5	3380	1	260	10	1.185
228	1.5	3500	1	260	10	1.226
250	1.5	3830	0.8	290	10	1.338
254	1.5	3890	0.8	290	10	1.359
265	1.5	4055	0.7	300	10	1.415
279	1.5	4265	0.7	320	10	1.487
305	1.5	5680	0.7	350	10 m pz. straight	1.007
320	1.5	5955	0.7	-	10 m pz. straight	1.105
350	1.5	6500	0.7	-	10 m pz. straight	1.313
400	1.5	7415	0.7	-	6 m pz. straight	1.020
406	1.5	7525	0.7	-	6 m pz. straight	1.050
450	1.5	8325	0.3	-	6 m pz. straight	1.283
500	1.5	9240	0.2	600	5 m pz. straight	1.313

The technical data here reported has been measured at 23 °C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu