

Black PVC-P Fuel Hose Datasheet

Product Code: RC07-I-112

Product Description

Transparent PVC-P hose, reinforced with a red anti-shock rigid PVC spiral.

Technical Specification

∅ INT.	Min Wall Thickness	Max Wall Thickness	Weight	W.P.	B.P.	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	bar	bar	m H ² O	mm	m	m ³
19.1	3.2	3.5	290	9	27	10	110	50	0.084
20	3.2	3.5	300	9	24	10	110	50	0.104
25	3.3	3.7	390	8	24	10	170	50	0.083
30	3.5	3.9	490	8	21	10	190	50	0.121
31.8	3.5	3.9	510	7	21	10	230	50	0.127
35	3.7	4.2	590	7	21	10	230	50	0.167
38.1	4.1	4.5	710	7	21	10	260	50	0.211
39	4.1	4.6	740	7	21	10	265	50	0.216
40	4.1	4.6	750	7	21	10	270	50	0.220
45	4.4	4.9	910	7	21	10	310	50	0.237
50	4.7	5.3	1090	6	18	10	350	50	0.349
51.5	4.8	5.3	1130	6	18	10	360	50	0.358
50.8	4.7	5.3	1100	6	18	10	350	50	0.354
55	5	5.5	1260	6	18	10	370	50	0.570
60	5.2	5.8	1440	6	18	10	415	50	0.619
63.5	5.5	6.1	1620	6	18	10	440	50	0.654
65	5.5	6.1	1660	6	18	10	450	50	0.667
70	5.6	6.3	1780	5	15	10	480	50	0.714
76.2	5.7	6.3	1950	5	15	10	525	50	0.767

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Specification

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	W.P.	B.P.	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	bar	bar	m H ² O	mm	m	m ³
80	6.1	6.8	2180	5	15	10	555	30 (JP 30/50)	0.674
90	6.1	7.1	2570	5	15	10	630	30	0.750
100	7.3	8.1	3270	5	15	9	695	30	0.892
102	7.3	8.1	3330	5	15	9	695	30	0.908
110	7.4	8.2	3610	4	12	9	780	30	1.294
120	7.8	8.6	4160	4	12	9	900	30	1.405
127	7.7	8.6	4350	4	12	9	1000	30	1.730
51.5	9.3	10.3	6340	4	12	8.5	1300	20	1.666
152.8	9.3	10.3	6390	4	12	8.5	1300	20	1.679
200	11.2	13.2	10350	4	12	8	2100	10	2.192
203.2	11.2	13.2	10510	4	12	8	2100	10	2.223

The technical data here reported has been measured at 23°C with 50% humidity.

The sizes highlighted in green are from our stock in Italy - subject to 2/3 weeks lead time.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.