

Transparent TPU PVC Spiral Antistatic Hose Datasheet

Product Code: RC07-I-124

Product Description

Transparent spiral hose, made with a special ester-based TPU wall with permanent antistatic properties.

Technical Specification

Ø INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	m H ² O	mm	m	m ³
13	0.4	2.8	80	2.5	20	20	0.013
16	0.4	2.8	100	2.5	25	20	0.018
19.1	0.4	2.8	120	2.5	25	20	0.022
20	0.4	2.8	120	2.5	25	20	0.025
22	0.4	2.8	130	2.5	28	20	0.028
25	0.4	2.8	150	2.5	30	20	0.034
30	0.4	2.8	170	2.5	35	20	0.051
31.8	0.4	2.9	190	2	35	20	0.054
35	0.5	3	220	2	45	20	0.059
38.1	0.5	3.1	250	2	50	20	0.064
40	0.5	3.1	260	2	60	20	0.067
45	0.5	3.2	300	2	65	20	0.099
50	0.5	3.4	350	2	70	20	0.11
50.8	0.5	3.4	360	2	70	20	0.11
55	0.5	3.6	420	2	75	20	0.12
60	0.5	3.8	500	1.6	80	20	0.17
63.5	0.5	3.9	550	1.6	80	20	0.18
65	0.5	3.9	560	1.6	90	20	0.19
70	0.6	4.2	600	1.6	95	30	0.34
76.2	0.6	4.2	650	1.6	100	30	0.37
80	0.6	4.5	690	1.6	110	30	0.38
90	0.6	4.6	800	800	125	30	0.43
100	0.6	4.8	870	870	140	30	0.63
102	0.6	4.8	880	880	140	30	0.64

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Technical Specification

∅ INT.	Min Wall Thickness	Max Wall Thickness	Weight	Vacuum	Bending	Coil Length	Volume
mm	mm	mm	g/m	m H ² O	mm	m	m ³
110	0.6	5.1	1010	1.2	150	30	0.69
120	0.6	5.4	1210	1	160	30	0.75
127	0.6	5.4	1270	1	170	30	0.79
130	0.7	5.7	1460	0.9	170	20	0.61
140	0.7	5.7	1560	0.9	180	20	0.65
151.5	0.7	5.8	1620	0.8	200	20	0.94
152.4	0.7	5.8	1630	0.8	200	20	0.84
160	0.7	7.2	2080	0.7	220	20	0.89
180	0.7	7.2	2330	0.4	250	20	1.49
200	0.7	7.2	2400	0.4	260	20	1.65
203.2	0.7	7.2	2440	0.4	260	20	1.67
250	0.8	8	3620	0.4	300	10	1.36
300	0.8	8.2	4500	0.3	350	10	1.62

The technical data here reported has been measured at 23°C with 50% humidity.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.