

DiamondPath Datasheet

Product Code: RC04195

Product Description

This lightweight matting is designed for convenient use at construction or factory sites, offering easy deployment. Its flexible nature allows it to conform to uneven surfaces effortlessly. Featuring a diamond-patterned top surface in a vibrant yellow color, it ensures high visibility for designated walkways. The matting is easily maintainable, as it can be cleaned using a jet washer or hose. Supplied in long rolls, installation is simple and adaptable— it can either be laid loosely or adhered to the floor. With its low profile, it effectively minimises the potential for tripping hazards.



Anti-Slip



Chemical-Resistant



Anti-Fatigue



Low Maintenance

Technical Specification

Property	Test Method	Value
Hardness (Shore A)	DIN ISO 7619-1	85 ±5
Volume Weight	DIN 53504	1.82g/cm ³
Tensile Strength	ASTM D412-16	Direction 1 - 1690psi / direction 2 - 1940psi
Elongation at Break	ASTM D3574-17	190%
Puncture Resistance	-	EN388:2016+A1:2028
Indentation Resistance	ASTM F970-17	
Temperature Range	°C	-10°C to +65°C
Size:		
Sheet Size:	Weight:	Thickness
1m x 10m	35kg	2mm



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.