FC40 Polyurethane Sealant Material Safety Data Sheet

Product Code: RC13102

Printing date 12.09.2018 *Revision: 12.09.2018*

*

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· **1.1 Product identifier**

· **Trade name: FC40**

· **Article number:** 74088

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **1.2.1 Relevant identified uses**

· **Sector of Use**
SU3 Industrial uses: uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU21 Consumer uses: Private households / general public / consumers

· **Product category** PC1 Adhesives, sealants

· **Process category** PROC4 Chemical production where opportunity for exposure arises

· **Environmental release category** ERC5 Use at industrial site leading to inclusion into/onto article

· **Application of the substance / the preparation :** Polyurethane sealant

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Trade Grade Products Ltd
10 Victory Close
Woolsbridge Ind Park
Three Legged Cross
Wimborne, Dorset, BH21 6SX
Phone: 01202 820177
Fax: 01202 814011
email: sales@thegluepeople.co.uk

· **Information department:** Laboratory

· **1.4 Emergency telephone number:** ORFILA: +33 (0)1 45 42 59 59 (in France)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**
The product is not classified, according to the CLP regulation.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008** Void

· **Hazard pictograms** Void

· **Signal word** Void

· **Hazard statements** Void

· **Additional information :**
Contains reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.
Safety data sheet available on request.
Contains isocyanates. May produce an allergic reaction.

· **Classification system** Non-irritating to rabbit's eye (method : OECD guideline 405)

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

(Contd. of page 1)

*

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· **Description:** Adhesive containing a polyurethane prepolymer based on diphenylmethanediisocyanate

· **Dangerous components:**

CAS: 9002-86-2	polyvinyl chloride substance with a Community workplace exposure limit	20-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2-5%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17	titanium dioxide substance with a Community workplace exposure limit	<5%
CAS: 1305-78-8 EINECS: 215-138-9 Reg.nr.: 01-2119475325-36	calcium oxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	<2.5%
CAS: 1309-37-1 EINECS: 215-168-2 Reg.nr.: 01-2119457614-35	diiron trioxide substance with a Community workplace exposure limit	<2%
EC number: 926-141-6 Reg.nr.: 01-2119456620-43	hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1, H304	<2%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	<2%
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45	calcium dihydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315	<0.5%
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32	carbon black substance with a Community workplace exposure limit	<0.5%
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47	4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	<0.1%

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information** Immediately remove any clothing soiled by the product.
· **After inhalation**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness, place patient stably in side position for transportation.
· **After skin contact** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
· **After swallowing** Do not induce vomiting; call for medical help immediately.
· **4.2 Most important symptoms and effects, both acute and delayed**
Drowsiness
Headache

(Contd. on page 3)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation.
We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu

Trade name: FC40

(Contd. of page 2)

Dizziness
Nausea
· ***4.3 Indication of any immediate medical attention and special treatment needed***
No further relevant information available.

SECTION 5: Firefighting measures

· ***5.1 Extinguishing media***
· ***Suitable extinguishing agents***
Carbon dioxide
Foam
Fire-extinguishing powder
· ***For safety reasons unsuitable extinguishing agents*** *Water with full jet.*
· ***5.2 Special hazards arising from the substance or mixture***
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NOx)
In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen cyanide (HCN)
Isocyanates
· ***5.3 Advice for firefighters***
· ***Protective equipment:*** *Wear self-contained respiratory protective device.*

SECTION 6: Accidental release measures

· ***6.1 Personal precautions, protective equipment and emergency procedures***
Ensure adequate ventilation.
Keep away from ignition sources.
· ***6.2 Environmental precautions:*** *Do not allow product to reach sewage system or any water course.*
· ***6.3 Methods and material for containment and cleaning up:***
Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
Do not close them (reaction with water forming carbon dioxide).
· ***6.4 Reference to other sections***
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· ***7.1 Precautions for safe handling*** *Ensure good ventilation/exhaustion at the workplace.*
· ***Information about protection against explosions and fires:***
Keep ignition sources away - Do not smoke.

· ***7.2 Conditions for safe storage, including any incompatibilities***
· ***Storage***
· ***Requirements to be met by storerooms and receptacles:*** *Provide ventilation for receptacles.*
· ***Information about storage in one common storage facility:*** *Not required.*
· ***Further information about storage conditions:***
Keep receptacle tightly sealed.
Store in dry conditions.
Store in a cool place.

(Contd. on page 4)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation.
We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

*

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **8.1 Control parameters**

· **Components with limit values that require monitoring at the workplace:**	
9002-86-2 polyvinyl chloride	
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust
1330-20-7 xylene, mixture of isomers	
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
13463-67-7 titanium dioxide	
WEL	Long-term value: 10* 4** mg/m³ *total inhalable **respirable
1305-78-8 calcium oxide	
WEL	Long-term value: 2 mg/m³
1309-37-1 diiron trioxide	
WEL	Short-term value: 10* mg/m³ Long-term value: 5* 10** 4*** mg/m³ *fume (as Fe),**total respirable,***respirable
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
RCP-TWA	Long-term value: 1200 mg/m³
VME	Long-term value: 1200 mg/m³
100-41-4 ethylbenzene	
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
1305-62-0 calcium dihydroxide	
WEL	Long-term value: 5 mg/m³
1333-86-4 carbon black	
WEL	Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³
101-68-8 4,4'-methylenediphenyl diisocyanate	
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO

· **Ingredients with biological limit values:**	
1330-20-7 xylene, mixture of isomers	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu

(Contd. of page 4)

· ***8.2 Exposure controls***
· ***Personal protective equipment***
· ***General protective and hygienic measures***
Wash hands before breaks and at the end of work.
Avoid close or long term contact with the skin.
· ***Breathing equipment:***
Use suitable respiratory protective device in case of insufficient ventilation:
Short term filter device:
Filter AB
· ***Protection of hands:***
PVA gloves of superior quality.
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· ***Eye protection:*** *Not required.*

*

SECTION 9: Physical and chemical properties

· ***9.1 Information on basic physical and chemical properties***	
· ***General Information***	
· ***Appearance:***	
Form:	*Pasty*
Colour:	*Various colours cherry*
· ***Odour:***	*Light*
· ***Change in condition***	
Melting point/freezing point:	*undetermined*
Initial boiling point and boiling range:	*137 °C*
· ***Flash point:***	*40-55 °C*
· ***Flammability (solid)***	*The product is not subject to classification because its speed of combustion is lower than the limit of the regulation.*
· ***Self-ignition temperature:***	*> 200 °C*
· ***Explosive properties:***	*Product is not explosive. However, formation of explosive air/vapour mixtures are possible*
· ***Explosion limits:***	
Lower:	*0.6 Vol %*
Upper:	*8 Vol %*
· ***Density at 20 °C:***	*1.16*
· ***Solubility in / Miscibility with***	
Water:	*Insoluble*
· ***9.2 Other information***	*No further relevant information available.*
· ***Volatile organic compounds (VOC) :***	*<9%*

SECTION 10: Stability and reactivity

· ***10.1 Reactivity*** *No further relevant information available.*

(Contd. on page 6)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

(Contd. of page 5)

· ***10.2 Chemical stability***
· ***Thermal decomposition / conditions to be avoided:***
No decomposition if used according to specifications.
· ***10.3 Possibility of hazardous reactions***
Reacts with alcohols, amines, aqueous acids and alkalis.
Reacts with water forming carbon dioxide.Danger of receptacles bursting because of vapour overpressure.
· ***10.4 Conditions to avoid*** *No further relevant information available.*
· ***10.5 Incompatible materials:*** *No further relevant information available.*
· ***10.6 Hazardous decomposition products:*** *No dangerous decomposition products known.*

*

SECTION 11: Toxicological information

· ***11.1 Information on toxicological effects***
· ***Acute toxicity*** *Based on available data, the classification criteria are not met.*

· **LD/LC50 values that are relevant for classification:**		
1330-20-7 xylene, mixture of isomers		
Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	6,350 mg/l (rat)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)

· ***Primary irritant effect:***
· ***Skin corrosion/irritation*** *May be slightly irritant.*
· ***Serious eye damage/irritation*** *May be slightly irritant.*
· ***Respiratory or skin sensitisation*** *Based on available data, the classification criteria are not met.*
· ***Additional toxicological information:*** *Non-irritating to rabbit's eye (method : OECD guideline 405)*
· ***CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)***
· ***Germ cell mutagenicity*** *Based on available data, the classification criteria are not met.*
· ***Carcinogenicity*** *Based on available data, the classification criteria are not met.*
· ***Reproductive toxicity*** *Based on available data, the classification criteria are not met.*
· ***STOT-single exposure*** *Based on available data, the classification criteria are not met.*
· ***STOT-repeated exposure*** *Based on available data, the classification criteria are not met.*
· ***Aspiration hazard*** *Based on available data, the classification criteria are not met.*

*

SECTION 12: Ecological information

· ***12.1 Toxicity***
· ***Aquatic toxicity:*** *No further relevant information available.*
· ***12.2 Persistence and degradability*** *No further relevant information available.*
· ***12.3 Bioaccumulative potential*** *No further relevant information available.*
· ***12.4 Mobility in soil*** *No further relevant information available.*
· ***Additional ecological information:***
· ***General notes:***
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow product to reach ground water, water course or sewage system.
· ***12.5 Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable.*
· ***vPvB:*** *Not applicable.*

(Contd. on page 7)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu

Trade name: FC40

(Contd. of page 6)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must be disposed of in an incinerator for hazardous waste according to official regulations.
· **Waste disposal key:** 08 04 09*

· **Uncleaned packaging :**
· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number** · **ADR, ADN, IMDG, IATA**	Void
· **14.2 UN proper shipping name** · **ADR, ADN, IMDG** · **IATA**	Void Not regulated
· **14.3 Transport hazard class(es)** · **ADR, ADN, IMDG, IATA** · **Class**	Void
· **14.4 Packing group** · **ADR, IMDG, IATA**	Void
· **14.5 Environmental hazards:**	Not applicable.
· **14.6 Special precautions for user** · **Stowage Category**	Not applicable. B
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **Transport/Additional information:**	Not classified as hazardous for transport as specified in paragraphs 2.2.41.1.5 of the ADR code, 2.4.2.2.2.1 of the IMDG code and 3.4.1.1.2.1 of the IATA code as the product is a solid and as its combustion speed is lower than 2.2 mm/s
· **UN "Model Regulation":**	Void

*

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **National regulations**
· **French VOC regulation (decree n° 2011-321) :** Class A+

(Contd. on page 8)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: FC40

(Contd. of page 7)

· **Biocides regulation (UE/2012/528)**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This data sheet is particularly in accordance with the european regulations 1907/2006/EC, 1272/2008/EC and their amendments ; it is written according to annex II of the european regulation 830/2015/EC.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Laboratory
· **Contact:** cf. § 1
· **Review :**
An asterisk in the margin of a paragraph means amendments in comparison to the former version.
· **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. on page 9)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation.
We hereby reserve the right to change the technical information herewith without notification or prior agreement.

(Contd. of page 8)

*

Annex: Exposure scenario

· **Name** *xylene, mixture of isomers*
· **Short title of the exposure scenario**
Industrial use for rigid foam, coatings and adhesives and sealants
Professional end use in rigid foam, coatings, adhesives and sealants and other composite material
Consumer end use in rigid foam, coatings and adhesives and sealants
· **Sector of Use**
SU3 Industrial uses: uses of substances as such or in preparations at industrial sites
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU3 Industrial uses: uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU21 Consumer uses: Private households / general public / consumers
· **Product category**
PC1 Adhesives, sealants
PC32 Polymer preparations and compounds
· **Process category**
PROC4 Chemical production where opportunity for exposure arises
PROC5 Mixing or blending in batch processes
PROC7 Industrial spraying
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
PROC15 Use as laboratory reagent
· **Environmental release category**
ERC2 Formulation into mixture
ERC5 Use at industrial site leading to inclusion into/onto article
ERC8c Widespread use leading to inclusion into/onto article (indoor)
ERC8f Widespread use leading to inclusion into/onto article (outdoor)
· **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
· **Conditions of use**
Customary application according to section 1.
According to directions for use.
· **Duration and frequency**
SU3 and SU22 :
Up to 8 h per day, 300 days per year
SU21, PC1 (adhesives, sealants) :
Up to 1 times per day, 365 days per year
Concentrations up to 25 %
Exposed skin surface (hands) up to 35.73 cm²
Amounts used/applied per event : 75 g
Room volume : > 20 m³
Exposition up to 1 hour(s) per event
· **Physical parameters**
· **Physical state** *Fluid*
· **Concentration of the substance in the mixture** *Raw material.*
· **Other operational conditions**
· **Other operational conditions affecting environmental exposure**
Local fresh water dilution factor: 10
Local marine water dilution factor : 100

(Contd. on page 10)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu

Trade name: FC40

(Contd. of page 9)

· ***Other operational conditions affecting worker exposure***
Indoor application.
Outdoor application.
Do not breathe gas/vapour/aerosol.
Avoid contact with the skin, eyes and clothing.
Avoid contact with the skin.
· ***Other operational conditions affecting consumer exposure*** *Keep out of the reach of children.*
· ***Other operational conditions affecting consumer exposure during the use of the product***
Application temperature : room temperature
· ***Risk management measures***
· ***Worker protection***
SU3 :
Avoid direct contact with skin. Identify potential areas for indirect contact with the skin. Wear gloves (EN 374) if there is a risk of contact of the substance with the skin. Remove impurities / quantities immediately after spilling. Wash skin immediately after handling. Complete basic training of personnel, so that exposure is minimized and eventually the skin problems are reported. Other measures of skin protection are required, such as waterproof clothing and a protective mask during activities with high spread, leading to the likely significant release of aerosols (e.g. spraying).
Mixing operations (closed systems) : provide adequate general ventilation (not less than 3 to 5 air changes per hour).
Preparation of material for application / blending operations (open systems) : provide adequate controlled ventilation (10 to 15 air changes per hour).
Spray (automatic / robotic) : carry out in ventilated booth with laminar air flow.
Spray : ensure an adequate controlled ventilation (10 to 15 air changes per hour). Wear a respiratory protection (standard EN 140 with Type A filter or better).
Roller coating, spraying and flow coating : provide additional ventilation where emissions occur.
Storage with occasional controlled exposure : store substance in a closed system.
Cleaning : ensure an adequate controlled ventilation (10 to 15 air changes per hour)
SU 22 :
Avoid direct contact with skin. Identify potential areas for indirect contact with the skin. Wear gloves (EN 374) if there is a risk of contact of the substance with the skin. Remove impurities / quantities immediately after spilling. Wash skin immediately after handling. Complete basic training of personnel, so that exposure is minimized and eventually the skin problems are reported. Other measures of skin protection are required, such as waterproof clothing and a protective mask during activities with high spread, leading to the likely significant release of aerosols (e.g. spraying).
Preparation of material for indoor application : provide adequate controlled ventilation (10 to 15 air changes per hour); avoid activities with more than 1 hour exposure.
Preparation of material for outdoor application : ensure that exploitation takes place outdoors ; avoid activities with more than 1 hour exposure.
Indoor roller coating, spraying and flow coating : ensure adequate controlled ventilation (10 to 15 air changes per hour) ; wear respiratory protection (standard EN 140 with Type A filter or better).
Outdoor roller coating, spray and flow coating : ensure that the operation takes place outdoors, wear respiratory protection (standard EN 140 with Type A filter or better).
Indoor spraying : carry out in ventilated booth with laminar air flow.
Outdoor spraying : ensure that the operation takes place outdoors ; avoid activities with more than 4 hours exposure ; wear a full face respirator according to standard EN136 with Type A filter or better.
Cleaning and maintenance of equipment : extinguish systems before opening and maintenance of equipment ; avoid activities with more than 4 hours exposure.
Storage with occasional controlled exposure : store substance in a closed system ; ensure an adequate controlled ventilation (10 to 15 air changes per hour).
Do not eat, drink, smoke while working.
· ***Organisational protective measures***
SU3 and SU 22 :
Do not apply industrial sludge to natural soils.
Sewage sludge has to be incinerated, stored or treated.

(Contd. on page 11)

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation.
We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Printing date 12.09.2018 Revision: 12.09.2018

Trade name: FC40

(Contd. of page 10)

Ensure that activities are executed by specialists or authorised personnel only.

· ***Technical protective measures***
Ensure good ventilation/exhaustion at the workplace.
Ensure that suitable extractors are available on processing machines
Take note of emission threshold.

· ***Personal protective measures***
Avoid contact with the eyes and skin.
Wear approved protective gloves (EN 374) ; if contamination of hands is likely,wash skin contamination immediately.
Do not inhale gases / fumes / aerosols.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Wear a respiratory protection (standard EN 140 with Type A filter or better).
Avoid contact with the skin.
Protective work clothing.

· ***Measures for consumer protection***
Ensure adequate labelling.
Protective gloves
Tightly sealed goggles.
Keep out of reach of children.
Keep locked up and out of the reach of children.

· ***Environmental protection measures***

· ***Air*** *No special measures required.*

· ***Water***
Do not allow to reach sewage system.
On-site wastewater treatment (before release into the water) to achieve the required level of cleaning : 93.6 %
Do not allow to reach ground water, water bodies or sewage system.

· ***Soil*** *Prevent contamination of soil.*

· ***Disposal measures***
Do not apply industrial sludge to natural soils.
Ensure that waste is collected and contained.

· ***Disposal procedures***
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· ***Guidance for downstream users***
For the risk assessment, the tools recommended by ECHA can be used.

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation.
We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E-mail: sales@rubbermanufact.com Http://www.rubbermanufact.com TeL:+86 18005162255
Nanjing YuHangrubber company limited in China Jiangshu