

High Grade EPDM Rubber Sheet – Sulphur Cured

Product Code: RC0302-SC

Product Description

A sulphur cured high grade EPDM rubber provides superior physical properties as standard when compared to the peroxide cured alternative. The superior tensile and tear strength create a material that is suitable for use in more physically demanding applications.



Available In -



Full Rolls

Cut to strip

Bespoke Gaskets

Technical Specification

Properties	Test Method	Values
Product		High Grade EPDM Rubber Sheeting
Compound		EPDM
Hardness (Shore A)		70° ± 5°
Density		1.30 g/cm ²
Tensile Strength		7 N/mm ²
Elongation at Break		250%
Compression Set (22h, 70°C)	DIN ISO 815	35%
Working Temperature Range		-40°C to + 100°C



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

Properties		
1mm x 1.4m x 20m		
1.5mm x 1.4m x 20m		
2mm x 1.4m x 20m		
3mm x 1.4m x 10m		
4mm x 1.4m x 10m		
5mm x 1.4m x 10m		
6mm x 1.4m x 10m		
8mm x 1.4m x 5m		
10mm x 1.4m x 5m		
12mm x 1.4m x 5m		
15mm x 1.4m x 5m		
20mm x 1.4m x 5m		
25mm x 1.4m x 5m		
30mm x 1.4m x 5m		
40mm x 1.4m x 5m		
50mm x 1.4m x 5m		



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.