

## Fuel Resistant Nitrile Sheeting Datasheet

Product Code: RC0344

### Product Description

Our fuel resistant nitrile and PVC blend is a premium grade material that has been specifically developed for use in fuel processing and transportation applications. This material also provides good abrasion and tear resistance as well as excellent flame and oil resistance. The material stability reduces contaminants while also providing superior life expectancy.

### Technical Specification



Available In -



Full Rolls

Cut to strip

Bespoke Gaskets

Properties	Test Method	Values
Product	-	Fuel Resistant Sheeting
Compound	-	NBR / PVC
Hardness (Shore A)	DIN 53505	65° ± 5°
Density	DIN 53508	1.25 g/cm <sup>2</sup>
Tensile Strength	DIN 53504	60 Kg/cm <sup>2</sup>
Elongation at Break	DIN 53504	250%
Tear Strength	DIN 53515	22 Kg/cm
Abrasion Resistance	DIN 53516	300 mm <sup>3</sup>
Compression Set (22hrs @ 70°C)	DIN 53517	35%
Working Temperature Range	-	-25°C to + 110°C



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

### Standard Sizes

Properties	Weight (Kg/m <sup>2</sup> )
1.5mm x 1.4m x 20m	1.88
3mm x 1.4m x 10m	3.75
6mm x 1.4m x 10m	7.50



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.