


Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Z50

Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

Technical Specification



Available In -

- Full Rolls
- Cut to strip
- Bespoke Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		Black
Compound		NR
Hardness (Shore A)		50° ± 5°
Density		1.15 g/cm ²
Tensile Strength		17 Mpa
Elongation at Break		500%
Abrasion Resistance		115 mm ³
Working Temperature Range		-20°C to +70°C



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

Standard Sizes

Stock Roll Sizes	Weight (Kg/m ²)
3mm x 1.4m x 10m	3.3
5mm x 1.4m x 10m	5.5
6mm x 1.4m x 10m	6.6



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.