

Marine Anti Slip Tape Datasheet

Product Code: RC3460

Key Features

- Excellent anti slip properties
- Designed specifically for marine use
- Excellent underfoot comfort
- Easy to install
- Easy to cut to size
- Self adhesive backing
- Highly durable

Potential Applications

- Decking
- Walkways
- Stairs / steps
- Entrances
- Diving boards



**ISO
9001 : 2015
REGISTERED**

Technical Specification

| Properties | Test Method | Data |
|-------------------------|------------------|----------------------------|
| Product | | Marine Anti Slip Tape |
| Back Carrier | Caliper Method | 0.04mm PVC |
| Adhesive Type | | Solvent Acrylic |
| Mineral Type | | S2 |
| Adhesion to Steel | PSTC-4 | 1500 g/25.4mm ² |
| Tensile Strength | PSTC-31 | 5 kg/25.4mm ² |
| Elongation Break Point | PSTC-31 | 5% |
| Temperature Range | Independent Test | -30°C to 70°C |
| Maximum Roll Size | | 1160mm x 100m |
| Resistance to Motor Oil | PSTC-35 | Excellent |
| Life Expectancy | PSTC-9 | 12 to 24 (Months) |

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.